

HQ:NSC36/tipless/AI BS

Tipless AFM Probe with 3 Different Soft Tapping Mode AFM Cantilevers


AFM probes of the HQ:NSC36 series have three different tipless soft tapping mode AFM cantilevers on one side of the holder chip. They can be used in various applications.

The HQ AFM probes offer high consistency of the AFM tip radius, the AFM cantilever reflectivity and the quality factor.

The aluminum reflective coating enhances the laser reflectivity of the AFM cantilevers by approximately 2.5 times.

Coating

Reflective Aluminum



AFM Probe Specifications

AFM Tip

SHAPE
Tipless

AFM Cantilever

CANTILEVER	SHAPE	FORCE CONST.	RES. FREQ.	LENGTH	WIDTH	THICKNESS
Cantilever A	Beam	1 N/m (0.1 – 4.6 N/m)*	90 kHz (30 – 160 kHz)*	110 μm (1 – 115 μm)*	32.5 μm (29.5 – 35.5 μm)*	1 μm (0.5 – 1.5 μm)*
Cantilever B	Beam	2 N/m (0.2 – 9 N/m)*	130 kHz (45 – 240 kHz)*	90 μm (1 – 95 μm)*	32.5 μm (29.5 – 35.5 μm)*	1 μm (0.5 – 1.5 μm)*
Cantilever C	Beam	0.6 N/m (0.06 – 2.7 N/m)*	65 kHz (25 – 115 kHz)*	130 μm (1 – 135 μm)*	32.5 μm (29.5 – 35.5 μm)*	1 μm (0.5 – 1.5 μm)*

* typical values