

## Product Description

SNOM fiber probes with glued quartz tuning-forks for NTEGRA line systems (NT-MDT Co.) with measuring head SNLG101NTF and Solver line systems with measuring head SNLG101.

Set of 10 SNOM probes with transmitted wavelength 400-550nm.

- Material - single mode optical fiber Nufern 405HP.
- Probe tip is coated by Al (70nm)/sublayer Cr (20nm) .
- Aperture (hole uncoated by Al) ~ 50-100 nm
- Angle of fiber - about 20 degrees
- Maximum optical input power - 400 microWatt
- Tip is formed by chemical etching.
- Fiber length ~ 2 meters.
- Tip length without protective coating is 7-8mm.

### Geometrical & Mechanical fiber Specifications:

Clad Diameter	125.0 ± 1.5 µm
Coating Diameter	245 ± 15 µm
Core-Clad Concentricity	< 0.5 µm
Coating/Clad Offset	≤ 5 µm
Coating Material	UV Cured, Dual Acrylate
Operating Temperature	-55 to +85 °C
Short-Term Bend Radius	≥ 6 mm
Long-Term Bend Radius	≥ 13 mm
Proof Test Level	≥ 200 kpsi (1.4 GN/m <sup>2</sup> )

### General Features

Basic Nufern fiber	405-HP
Operating wavelength	400-550 nm
Second Mode Cut-Off	370 ± 20 nm
Measured Optical efficiency at the wavelength 530nm	5x10 <sup>(-6)</sup> - 5x10 <sup>(-5)</sup>
Calculated Optical efficiency at the working wavelength	10 <sup>(-5)</sup> - 5x10 <sup>(-4)</sup>