

Product description

Platinum Silicide Probes Non-Contact / Tapping Mode - High Resonance Frequency

NANOSENSORS™ PtSi-NCH probes are designed for non-contact mode or tapping mode AFM (also known as: attractive or dynamic mode). This AFM probe type combines high operation stability with outstanding sensitivity and fast scanning ability.

For applications that require a wear resistant and an electrically conductive AFM tip we recommend this type. NANOSENSORS™ PtSi-FM probes are suitable for C-AFM, Tunneling AFM and Scanning Capacitance Microscopy (SCM).

The Platinum Silicide coating shows an excellent conductivity (almost approaching metal conductivity). The typical AFM tip radius of curvature is around 25 nm.

The AFM probe offers unique features:

- platinum silicide coating with excellent conductivity and good wear-out behavior
- high mechanical Q-factor for high sensitivity
- alignment grooves on backside of silicon holder chip

This AFM probe features alignment grooves on the back side of the holder chip. These grooves fit to the NANOSENSORS Alignment Chip.

Cantilever data:

Property	Nominal Value	Specified Range
Resonance Frequency [kHz]	330	204 - 497
Force Constant [N/m]	42	10 - 130
Length [μm]	125	115 - 135
Mean Width [μm]	30	22.5 - 37.5
Thickness [μm]	4	3 - 5

Order codes and shipping units:

Order Code	AFM probes per pack	Data sheet
PtSi-NCH-10	10	of all probes
PtSi-NCH-20	20	of all probes
PtSi-NCH-50	50