

# Tap150-G

## AFM Tip

SHAPE	HEIGHT	SETBACK	RADIUS	HALF CONE ANGLE
Rotated	17 $\mu\text{m}$ (15 – 19 $\mu\text{m}$ )*	15 $\mu\text{m}$ (10 – 20 $\mu\text{m}$ )*	10 nm	20°–25° along cantilever axis, 25°–30° from side, 10° at the apex

## AFM Cantilever

Cantilever A	
Shape	Beam
Force Constant	5 N/m (1.5 – 15 N/m)*
Resonance Frequency	150 kHz (75 – 225 kHz)*
Length	125 $\mu\text{m}$ (115 – 135 $\mu\text{m}$ )*
Width	25 $\mu\text{m}$ (20 – 30 $\mu\text{m}$ )*
Thickness	2.1 $\mu\text{m}$ (1.1 – 3.1 $\mu\text{m}$ )*

\* typical range

## Coating

Uncoated

## Alignment Grooves

This product features alignment grooves on the back side of the holder chip.

## Additional Info

Monolithic silicon AFM probe for soft tapping mode operation.

The rotated AFM tip allows for more symmetric representation of high sample features. The consistent AFM tip radius ensures good resolution and reproducibility.

The AFM holder chip fits most commercial AFM systems as it is industry standard size.